	1		2			3		4		5		6	
									Product NO.				
									REV A	DESCRIPTION First issue	DWN Mr.chen	DATE 2016/03/17	APPROVEN John kine
										•			
A													
	La contraction of the second s												
		<b>K</b>											
					14	4,60							
			t t										
В								××					
								***			]		
			ហ					***				0	
			ø14.5	+	- + -\'	\- +===		×			+	ø9.50	
			Ø									ø	
						=					50		
						/					A M M M		
	<u>SPECIFICA</u>				5.7								
	Impedance: 50			-k									
	Frequency Ran	ige:DC 6G		T									-
	VSWR:1.3max Working Volta	ac:500v RMS	SFA Lovel					37.50					
	Insulation Re			L									
Temperature Range: $-40^{\circ}$ TO $+140^{\circ}$													
	Drawings prod			ROHS	standards	5							
				1	NOTE:	I							
3					NUIE:		Τ.1		. 10 . 20				
7							Tolerance	$30-120$ $\pm$	0.30	RENHOTEC RE		LO GR	
3					DRAWN	2016/03/		Angular ±2°		ne: BNC PLUG			
E 4	CONTACT PIN	BRASS	GOLD	1	Zelin.Zhang CHECKED	5 17	View	$\bigcirc \square$		Bite Theo			DEV
2	INSULATOR BODY	TEFLON BRASS	NATURAL NEXCOTE				UNIT	MM		E Product NO. RHT-6			REV A
	DESCRIPTION	MATERIAL	FINISH	QTY	approvals John	17/03.201	6SCALE	1:1	Date	ETime 2016/03/17	ILE company drawi	ngs/BD SHEE	T: 1 OF 1
	1		2		Kine	3		4		5		6	