


MCX Straight Plug for RG316 Cable 50ohm - RHT-617-1026



Drawing



Basic Information

Connector Type	Jack
Cable Type	RG316
Fastening Type	Push-in
Mounting Feature	Through Hole
Mounting Type	PCB Mount
Number of Ports	1
Orientation	Straight
Contact Type	Female Pin

Mechanical Specification

Termination	Solder
-------------	--------

Environmental Specification

Temperature Range	-65°C to +165°C
-------------------	-----------------

Material and Finish



Component Description	Material	Finish
Insulator	Teflon	
Shell	Brass	Gold Plated
Center Contact	Phosphor	Gold Plated
Ferrule	Brass	Nickel Plated

Impedance Testing

Impedance	50 ohm
-----------	--------

Frequency & VSWR Test Report

Frequency Range	6GHz
VSWR	1.25 MAX



Working Voltage & Insulation Resistance Test

Dielectric Withstanding Voltage	1000 VRMS Max
Insultation Resistance	5000 Ohms Min



Version History

REV	Date	Revise Contents	Drafter	Approver
A.0	2026.7.10	The initial formulation	Esther	Joson

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.